

Model: NR-8066-IPC50 Series

NETRA 5.0 Megapixels IR Box Network Camera



Features

- 1/2.5" 5.0 Megapixels Progressive Scan Aptina CMOS
- H.264 High Profile & MJPEG dual-stream encoding
- Max 12fps@2592x1944, and 20fps@2048x1536, 25/30fps@1080P (1920x1080)
- Digital WDR (>80db), 2D, 3D noise reduction, AWB, AGC, BLC
- Multiple network monitoring: Web viewer, CMS, Smart phone.
- Micro SD Card Slot (max 64GB).
- Support IR-CUT; To switch Day/Night by video detection or time or IR detection.
- 3.3-10.5mm varifocal lens or fixed lens 6mm, 8mm are optional
- Three big LED lights, IR distance about 20 meters.
- IP66.
- POE optional.


Specification

Ordering Model:	IR	IP66	POE	LENS (6, 8 mm or 3.3-10.5mm)
NR-8066-IPC50	Yes	Yes	No	Fixed Lens included, 3.3-10.5mm optional
NR-8066-IPC50-POE	Yes	Yes	Yes	Fixed Lens included, 3.3-10.5mm optional
Camera				
Image Sensor	1/2.5" 5.0 megapixels Progressive Aptina CMOS			
Effective Pixels	2592x1944			
Scanning System	Progressive			
Electronics Shutter Speed	Auto (1/25, 1/30 ~ 1/10000s)			
Min. Illumination	1Lux/F1.2 (Color), 0.1Lux/F1.2(B/W); 0Lux/F1.2 (IR on)			
S/N Ratio	>50dB			
Camera Features				
Max. IR LEDs Length	15-20 m			
Day/Night Switch	Auto Color to B/W			
Backlight Compensation	BLC / HLC / WDR (digital)			
White Balance	Auto			
Gain Control	Auto			
Noise Reduction	2D, 3D			
Privacy Masking	Up to 4 Areas			
Lens				
Focal Length	6mm, 8mm or 3.3-10.5mm optional			
Max Aperture	F1.4			
Focus Control	Manual			
Angle of View	80° ~ 20°			
Lens Type	Manual Iris			
Mount Type	Board-in Type			
Video				
Compression	H.264 High profile, Main Profile, Baseline / MJPEG			
Resolution	2592x1944, 2048x1536 ; 1920x1080, 640x352, 320x240			
Frame Rate	Preferred Stream	2592x1944 (1~12fps), 2048x1536 (1~20fps), 1920x1080 (1~25/30fps),		
	Alternate Stream	640x352, 320x240 (1~25/30fps)		
Bit Rate	32KB ~ 16Mbps, support VBR, CBR			
Network				
Ethernet	RJ-45 (10/100Base-T)			
Protocol	IPv4/IPv6, HTTP, TCP/IP, UDP, RTP, RTCP, UPNP, RTSP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP,			
ONVIF	ONVIF Ver. 2.4			
Max. User Access	5 users			
Smart Phone	iPhone, iPad, Android, Symbian			


Model: NR-8066-IPC50 Series

General	
Power Supply	DC12V, POE (802.3af)
Power Consumption	≤9W
Working Environment	-20 °C ~60°C
Ingress Protection	IP66,
Dimensions	318mm ×110mm×90mm
Weight	0.7KG

Dimensions (mm)



Interfaces :



Installation:

