



Model: NR-8063-IPC30 Series

---

## 3.0 Megapixels IR Box Network Camera



### Features

- 1/2.5" 3.0 Megapixels Progressive Scan Aptina CMOS
- H.264 High Profile & MJPEG dual-stream encoding
- Max 20fps@2048x1536, 25/30fps@1080P (1920x1080)
- Digital WDR (>100db), 2D, 3D noise reduction, AWB, AGC, BLC
- Multiple network monitoring: Web viewer, CMS, Smart phone.
- Support IR-CUT; To switch Day/Night by video detection or time or IR detection.
- 3.0-10.5mm varifocal lens or fixed lens 6mm, 8mm, 12mm are optional
- Max. IR LEDs Length 30-50m
- IP66,
- Micro SD Card Slot (max 64GB),
- POE optional.
- Support ONVIF 2.4.



Model: NR-8063-IPC30 Series

## Specification


Model	IR	IP66	POE	LENS (6, 8, 12mm or 3.0-10.5mm)
<b>NR-8063-IPC30</b>	Yes	Yes	No	Fixed Lens included, 3.0-10.5mm optional
<b>NR-8063-IPC30-POE</b>	Yes	Yes	Yes	Fixed Lens included, 3.0-10.5mm optional
<b>Camera</b>				
Image Sensor	1/2.5" 3.0megapixels Progressive Scan Aptina CMOS			
Effective Pixels	2048x1536			
Scanning System	Progressive			
Electronics Shutter Speed	Auto (1/25,1/30 ~ 1/10000s)			
Min. Illumination	1Lux/F1.2 (Color), 0.1Lux/F1.2(B/W); 0Lux/F1.2 (IR on)			
S/N Ratio	>50dB			
<b>Camera Features</b>				
Max. IR LEDs Length	30-50m			
Day/Night	Auto (ICR) / Color / B/W			
Backlight Compensation	BLC / HLC / WDR (digital)			
White Balance	Auto			
Gain Control	Auto			
Noise Reduction	2D, 3D			
Privacy Masking	Up to 4 Areas			
<b>Lens</b>				
Focal Length	6mm, 8mm, 12mm, or 3.0-10.5mm optional			
Max Aperture	F1.4			
Focus Control	Manual			
Angle of View	80°~ 20°			
Lens Type	Manual Iris			
Mount Type	Board-in Type			
<b>Video</b>				
Compression	H.264 High Profile, Main Profile, Baseline / MJPEG			
Resolution	2048x1536 ; 1920x1080, 640x352, 320x240			
Frame Rate	Preferred Stream	2048x1536 (1~20fps), 1920x1080 (1~25/30fps),		
	Alternate Stream	640x352, 320x240 (1~25/30fps)		
Bit Rate	32KB ~16Mbps, support VBR, CBR			
<b>Network</b>				
Ethernet	RJ-45 (10/100Base-T)			
Protocol	IPv4/IPv6, HTTP, TCP/IP, UDP, RTP, RTCP, UPNP, RTSP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP,			
ONVIF	ONVIF Ver. 2.4			
Max. User Access	10 users			
Smart Phone	iPhone, iPad, Android, Symbian			
<b>General</b>				



Model: NR-8063-IPC30 Series

Power Supply	DC12V, POE (802.3af)
Power Consumption	≤10W
Working Environment	-20 °C ~ 60°C
Ingress Protection	IP66,
Dimensions	220mm ×117.5mm ×111mm
Weight	2.2KG

### Dimensions (mm)



### Interfaces :

