

MINI NVR 9CH 3MP/4CH 5MP 1HDD

Model : NR-N6200-9EH

- Desktop Installation, Mini II 1HDD(2,5 inches) NVR, Support 4T HDD;
- P2P cloud service, including cloud connecting, cloud monitoring, cloud transmitting to access IPC and NVR at any time and any place
- Support Onvif protocol, support High profile S, High profile G, compatible with different IP camera that based on Onvif, RTSP standard
- Support megapixel HD network video preview, storage and playback;
- Support search, playback and backup by event;
- Support all channel image display on one screen at same time, support 4 channels' image display by mainstream, and 4 channels playback;
- Support monitor PTZ on preview mode
- Offer CMS for free

Front Panel :



Key Features :

- P2P cloud service, including cloud connecting, cloud monitoring, cloud transmitting to access IPC and NVR at any time and any place
- Support Onvif protocol, support High profile S, High profile G, compatible with different IP camera that based on Onvif, RTSP standard



- Support megapixel HD network video preview, storage and playback;
- Support search, playback and backup by event;
- Support all channel image display on one screen at same time, support 4 channels' image display by mainstream, and 4 channels playback;
- Support monitor PTZ on preview mode
- Offer CMS for free

Main Functions :

1. Preview channel can be switched to other channel randomly without changing the MAC which is convenient for the project construction;
2. The dendritic menu can be moved. Man-machine communication is more direct and the settings of parameters are more easy and convenient;
3. The mouse roller can realize 15X digital zooming which the enlarged image can be dragged and moved randomly under preview and playback modes;
4. Immediate snapshot and immediate view; the picture will be stored in an independent area in the HDD;
5. The recording playback is shown by time bar and different color represents different recording type. It is very fast and easy to find check the recording;
6. Recording backup can be accurate to second. Any time period of backup is available;
7. The recording files in the USB disk can play directly in the playback interface while the snapshot pictures can be viewed directly;
8. With 3G, WIFI wireless connection functions;
9. Standard resolution which can be adjusted according to the display device in order to get the best image quality;
10. Adopt HDD sequence writing method and the data is written from 0 track which increase 2.5X lifetime of the HDD

Model Number	NR-N6200-9EH
Operating System	Embedded LINUX operating system
Image Code Control	Image code quality adjustable, variable bitstream and constant bitstream optional
Dual Stream	Each channel can set main stream and sub stream
Video Standard	1080P(1920×1080)30fps/960P/(1280×960)/720P(1280×720)30fps
Monitoring Image Quality	1080P(1920×1080) / 960P/(1280×960)/720P(1280×720)
Image Motion Detection	Each screen can set multiple detection areas and set 6-level sensitivity
Recording Playback Quality	Any 9ch 960P playback, 4ch 5MP/3MP/1080P playback simultaneously
Region Cover	Every channel can set 4 cover regions (IPC Support)

Recording Mode	Support manual , auto, dynamic detection, alarm trigger record mode(Partly needs IPC Support)	
Backup Way	Support U disk, USB mobile HDD, USB DVD-RW. network storage and backup	
Operation Way	Mouse, Keyboard	
Local Login	Username and password	
Recording Storage	Local HDD, network	
External Ports	Video Input	①9×(1920*960)+sub[720*576]+4Ref.+9Play 9ch 1.3MP IP Camera
		②9×(2048*1536)+sub[960*576]+4Ref.+4Play 9ch 3.0MP IP Camera
		③9×(2592*1944)+sub[960*576]+4Ref.+1Play 9ch 5.0MP IP Camera
		/
	Audio Input	9ch network audio input
	Video Output	1ch VGA+1ch HDMI
	Network Port	1 RJ45,10M/100M/1000M self-adaptive LAN port
USB Port	2 USB 2.0 ports	
Wireless Port	WIFI	
HDD	HDD Port	1 2.5" SATA HDD Port + 1 E-SATA HDD Port
	MAX Capacity	Each port supports MAX 4TB HDD
Mobile Surveillance	Support(iPhone, Windows Mobile, BlackBerry, Symbian, Android) smart phone	
Power Supply	5V2A	
Power Consumption	≤10W (without HDD)	
Working Temperature	-10°C ~ + 55°C	
Working Humidity	10%-90%	